

Tesrol

STYLELITE HIGH GLOSS ACRYLIC
DOORS & PANELS



StyleLite[®]
by **EGR**

StyleLite High Gloss Acrylic

StyleLite® is the superior high gloss finish for all door, drawer and furniture construction.

StyleLite is the new high gloss finished sheet which provides a superior gloss appearance and lustre of that of glass. It also features a super hard surface that resists even the harshest treatment.

StyleLite is laminated to E0 MR MDF board. This is a low formaldehyde emitting MDF product that has a formaldehyde emission of less than 0.5mg/L, which is lower than the current Australian standard.

StyleLite provides a deep high gloss colour without ripples which makes it the only choice for discerning designers and architects.

StyleLite is technologically advanced and is manufactured using state of the art extrusion processes that deliver a quality in uniformity, hardness and colour integrity that is industry leading.



APPLICATIONS

StyleLite is suited for many different applications:

- Kitchen cabinets and doors
- Office Furniture and Partitions
- Entry and Passageway doors
- Wall cladding in retail outlets
- Wardrobe doors
- Entertainment and occasional furniture
- Shelving and Display cabinets

StyleLite is not recommended for outdoor use or where a direct heat source is applied.

FEATURES

- Ultra high gloss ripple free surface
- UV and colour fade protected
- High scratch resistance
- Won't chip, crack or delaminate
- Very easy to clean and maintain

ENVIRONMENT

StyleLite is fully recyclable by mechanical means. StyleLite sheet is manufactured and then laminated without the use of any VOC's or other harmful emissions. StyleLite is hygienic and does not promote bacterial growth or transmission.


METALLIC COLOURS

Metallic colours are directional. Take note of the arrows on the protective sheet. We recommend all panels are positioned with the arrows in one direction to avoid apparent shade or colour variation.


EDGE TAPE

A near seamless appearance can be achieved using StyleLite high gloss ABS colour matched edge tape. Many other contrast and dual colour tapes can be used to achieve a sophisticated and contemporary style.


Colours




FROST



ARCTIC



LACE




ALABASTER


Note: Due to the nature of the printing process, the colours and images depicted throughout this brochure may vary compared to the actual products' colour and results achieved. Images and colours are to be used as a guide only.

* METALLIC COLOURS


WOODGRAIN COLOURS




ASH




SAND




FOSSIL



SLATE




MOCHA




ESPRESSO




CHERRY



RUBY




CARBON



SILVER *



CHAMPAGNE *



GRAPHITE *



LAVATO OAK #



RIGA BIRCH #




SIENNA TEAK #



TULIPWOOD #



GLASSA CHERRY #



TIERRA ELM #

STANDARD BOARD OPTIONS

STOCK OFFER / BOARD OPTIONS

Board options	Panel Size	Thickness / Board	Lamination
Premium Offer	2400 x 1200	18mm MR MDF E0	PUR Laminated StyleLite 2 sided - Matching Colour on Face & Back (All Colours Available)
Wardrobe Offer	2400 x 1200	9mm MR MDF E0	PUR laminated StyleLite (Colours: Artic, Alabaster, Mocha & Carbon only) 1 sided - Colour on face & Arctic Gloss on back

TECHNICAL

- High gloss acrylic cap over colored ABS rated to an amazing level of hardness
- For manual and volume lamination using suitable adhesive systems on a variety of substrates
- Surface marks can be easily repaired
- Good Chemical resistance
- No special equipment for machining
- Matching edge bands are available
- High UV and heat resistance
- Economical and easy to use
- 2400mm x 1200mm sheet size

STYLELITE PROPERTIES & PERFORMANCE

Properties	Specification	Method
Gloss Level	> 90%	Viewed at 60°
Mass	13.5kg/m ²	N/A
Surface Hardness	2H - 3H	Pencil Hardness
Heat Distortion Temperature	85°C	ASTM D648
Service Temperature	70°C	Continuous
Fire Rating	Group 4	A2.4 BCA
Bond Strength	100N (25N min)	AS/nzs 4266.28
Surface Resistance	1.25 MPa (0.9 MPa min)	AS/nzs 4266.70
Stain Resistance	No effect	AS/nzs 4266.25
Steam Resistance	No change after 30 min	AS/nzs 4266.23
Cracking Resistance	No effect	AS/nzs 4266.24
Dry Heat Resistance	No loss of gloss or colour change	AS/nzs 4266.26

CLEANING

Best results are achieved by using a soft cloth or chamois with a non abrasive soap or detergent in warm water.

POLISHING

Minor scratches and scuffs can be easily removed from StyleLite by hand with selected liquid polishes and soft polishing cloths.

Tesrol

TESROL HEAD OFFICE

405 Victoria Street Wetherill Park, NSW 2164 Australia

T: 1300 837 765

F: 1300 837 775

E: sales@tesrol.com.au



StyleLite[®]

by **EGR**

1. Tesrol and EGR expressly disclaim any representations or warranties of any kind, whether express or implied, as to the accuracy, currency, completeness and/or the merchantability or fitness for a particular purpose of any information contained in or provided via this documentation and/or any service or product described or promoted in this document.
2. It is the customer's responsibility to thoroughly examine StyleLite by a qualified person, to determine whether it is suitable for the application it was purchased for.
3. The receiver of our products is fully responsible to check and to take into account possible third party's patent rights, as well as the existing laws in the country of installation prior to installing our product.
4. No liability may be derived from these images or statements nor from our free technical advice.
5. Tesrol and EGR reserve the right to change, add or remove colours or product without notice.
6. StyleLite is for indoor use only.
7. StyleLite and EGR are registered trademarks.
8. Images and colours should be used as a guide only.

www.tesrol.com.au